



# Electric Deadman Handle and Cable Assembly



Deadman

## DESCRIPTION

This electric deadman handle and cable assembly is used in conjunction with Scully overfill prevention and/or earth verification systems when regulations or operating procedures require the use of an operator held deadman switch.

The rugged deadman handle fits easily in the hand for maximum comfort. When the trigger is squeezed, an electric switch is activated. The handle itself is constructed of high performance Urethane and includes all stainless steel hardware for corrosion resistance.

10.6 meter (32 foot), 2-conductor coiled cable with petroleum resistant jacket material is provided for convenient connection to the Sculcon junction box.

## TECHNICAL SPECIFICATION

**Handle:** High performance Urethane body with stainless steel trigger.

**Cable:** 10.6 meter (32 foot), coiled cable with petroleum resistant jacket material.

**Switch Specs:** SPST normally open.

### Handle

**Dimensions:** 101mm X 44.45mm (4" x 1<sup>3/4</sup>").

**Weight:** .9kg (2 lb) including cable.

**Approvals:** These devices are compatible with IECEx/ATEX Intrinsically Safe systems as Simple Apparatus.

## ORDERING INFORMATION

Description	Part Number
Deadman Handle & Switch Assembly, Blk Coil Cable, 10.6 meter	08863
Strain Relief 90Deg 3/8" - Deadman Cable to Sculcon Box	32425

Copyright © 2023 Scully Signal Company. Dynacheck, Dynamic Self-Checking, Dynamic Self-Testing, Faylsafe, IntelliCheck, Intellitrol are registered trademarks of Scully Signal Company. All Rights Reserved. Specifications are subject to change without notice.

01-7A  
June 2023



**Scully Signal Company**  
800 272 8559  
sales@scully.com  
Wilmington, MA, USA

**Scully Systems Europe NV**  
+32 (0) 15 56 00 70  
sales@scully.be  
Mechelen, Belgium

**Scully UK Ltd**  
+44 (0) 1606 553805  
sales@scullyuk.com  
Winsford Cheshire, UK

**Scully Systems India**  
+91 9821799566  
salesindia@scully.com  
Maharashtra, India

