

The Scully Rack Tester is an advanced, comprehensive, portable tester approved for testing in hazardous locations. It allows Scully customers and field personnel to quickly assess any Scully overfill prevention, earthing and vehicle identification rack controller for proper equipment operation. In the event of a malfunction, it facilitates problem isolation and resolution.

## THE SCULLY UNIVERSAL RACK TESTER SIMULATES:

- Optic and Thermistor Overfill Sensors
- Scully Ground Bolts & Ground Balls
- Scully T.I.M.™ Truck Identification Modules

ORDERING INFORMATION	
Description	Part Number
Scully Rack Tester	09832

## **TECHNICAL SPECIFICATION**

**Power Supply:** Powered by loading rack control unit under test.

**Dimensions:** 27.432 cm long x 24.892 cm wide x 12.192 cm high. (10.8" long x 9.8" wide x 4.8" high).

Weight: 2.87 kg.

**Connection:** The rack controller plug connects to one of three style sockets on the front of the tester.

## **APPROVALS**

ITS14ATEX28108X II 1 G Ex ia IIB T4 Ga  $0^{\circ}$ C  $\leq$  Ta  $\leq$  +60 $^{\circ}$ C





Patent Number: 10260930

Copyright © 2023 Scully Signal Company. Dynacheck, Dynamic Self-Checking, Dynamic Self-Testing, Faylsafe, IntelliCheck, Intellitrol are registered trademarks of Scully Signal Company. All Rights Reserved. Specifications are subject to change without notice.

01-9A June 2023



