Setting Standards in Safety and Dependability since 1936.

The Ideal Commercial Delivery Nozzles with Increased Hose Flexibility and Freedom of Movement

- The leading choice for heavy product, high volume deliveries.
- Reduced pressure drop allows for faster pumping speeds.
- Prevents closing shock to prolong truck equipment life.
- Feature leak-proof filling and no-drip operation.
- Original ball valve design and deadbolt locking handle.
- Advanced ball bearing design allows for easy rotation at all operating pressures.
- Teflon high recovery seal and shielded bearings for optimum field performance.
- No nipple required to attach hose with male style swivels.
- Lightweight aluminum and zinc construction.
- Wide variety of liquid product use.

Materials

- Aluminum body.
- Hard chrome plated brass ball valve.
- Teflon ball seat.
- Delrin ball follower.
- Anodized aluminum swivel body.
- Teflon swivel seal.
- Viton seals.

Options

- Without swivel.
- Sightglass.
- Compatibility with special chemicals.

Consult Scully for part numbers



Flow Rates

• Used for deliveries up to 200 G.P.M.

Inlet Style	Inlet Thread	Outlet Thread	Part #
5 P.S.I. FEMALE	11/2"	1 _{1/2} " Female NPT	05917
5 P.S.I. FEMALE	2"	11/2" Female NPT	05919
5 P.S.I. FEMALE	2"	2" Female NPT	05924

Super Nozzle Tightfill Hose Swivels

Increased Hose Flexibility and Freedom of Movement

- Advanced ball bearing design allows for easy rotation at all operating pressures.
- Teflon high recovery seal and shielded bearings for optimum field performance.
- Lightweight aluminum and zinc construction.



Female Super Nozzle Swivel



Male Super Nozzle Swivel

Inlet Thread Style	Inlet Thread Size	Male Outlet Thread	Part #
FEMALE	11/2"	COM-B	05824
FEMALE	2"	COM-B	05826
MALE	2"	COM-B	05862
COM-B outlet thread screws d	lirectly into the Super Nozzle body only.		

Super Nozzle Outlets

Outlet Thread Style	Outlet Thread Size	Male Outlet Thread	Part #
FEMALE	11/2",NPT	COM-B	11118
FEMALE	2",NPT	COM-B	11167

Super Nozzle Non Swiveling Inlets

•	•		
Outlet Thread Style	InletThread Size	Male Outlet Thread	Part #
FEMALE	11/2", NPT	COM-B	11179
FEMALE	2",NPT	COM-B	11180

Super Nozzle Replacement Parts

Only genuine Scully replacement parts will ensure proper operation and prevent liabilities associated with spills.

· · · · · · · · · · · · · · · · · · ·	· r
Description	Part #
O-Rings for Nozzle Connector (Qty.3)	04318
Sight Glass	05420
Seal kit, No Swivel Parts	05933
Nozzle Rebuild Kit	05934
Bushing, for all Nozzles, BULK 10 (also sold 1 each- use Part # 10220)	10220BULK
Shim-Control Rod, for all Nozzles, BULK 25 (also sold 1 each- use Part # 10221)	10221BULK
Latch Plate, BULK 10 (also sold 1 each- use Part # 11595)	11595BULK
Control Rod, BULK 10 (also sold 1 each- use Part # 11602)	11602BULK
Handle & Latch Assembly Kit, BULK 5 (also sold 1 each- use Part # 11603)	11603BULK
Handle Upgrade Kit	11604
Outlet O-Ring, BULK 5 (also sold 1 each- use Part # 11298)	11298BULK
Anti-Drip Valve, 5PSI, BULK 5 (also sold 1 each- use Part # 11733)	11733BULK

Note: Handle & Latch Replacement parts for Early Super Nozzles pre 1981 are available. Contact Scully for details.







Bushing

10221BULK Shim-Control Rod





11595BULK Latch Plate



11602BULK Control Rod















Copyright © 2019 Scully Signal Company. Dynacheck, Dynamic Self-Checking, Dynamic Self-Testing, Faylsafe, Golden Gallon, IntelliCheck, Intellitrol, Mark IV, Mark V, Sculclamp, Sculflow, Sculmatic, Twis-Lok, Unifil, Ventafil, Ventalarm, V.I.P. and Whistler are registered trademarksof Scully Signal Company. All Rights Reserved. Specifications are subject to change without notice.





Self Locking Screw

· Control Rod Washer

Viton O Ring (4 Sizes)

Meridian House, Unit 33 37 Road One Winsford Industrial Estate, Winsford Cheshire CW7 3QG, UK +44 (0) 1606 553805 • sales@scullyuk.com

