



Unifil®

The Original and Ultimate Delivery Efficiency Equipment for Over Eighty Years

Setting Standards in Safety and Dependability since 1936.

Scully Unifil Tightfill Connections For Fast, Leak-Proof Deliveries



45° ADAPTOR

Male & Female. Ideally suited in cases where the fill pipe is very close to the wall.

Description	Model #	Size	Part #
Female UF-41	1 1/4"	04324	
Female UF-44	1 1/2"	04325	
Female UF-47	2"	04328	
Male UF-152	1 1/2"	04352	
Male UF-151	2"	04351	

STRAIGHT ADAPTOR

Male & Female. Used when replacing a pipe plug for 1 1/4", 1 1/2" and 2" fill pipes.

Female UF-65	1 1/4"	04336	
Female UF-65C	1 1/4" cored	04337	
Female UF-66	1 1/2"	04338	
Female UF-66C	1 1/2" cored	04339	
Female UF-67	2"	04340	
Female UF-67C	2" cored	04341	
Male UF-15	1 1/4"	04311	
Male UF-16	1 1/2"	04312	
Male UF-16C	1 1/2" cored	04313	
Male UF-17	2"	04314	
Male UF-17C	2" cored	04315	



ALL-WEATHER CAP

This cap fits the top of all Scully straight and 45° adaptors and features a new heavy weight design. No gasket is necessary.

UF-21	Fits All Scully Straight and 45° Adaptors	04316	
-------	---	-------	--

MALE SHOULDER ADAPTOR

Specially designed for installation in an existing fill box or coupling, or in any applications where a good watershed is desired around the joint. Available in 2" IPS size with standard threads (50S).

UF-50S	2" S	04332	
UF-50SC	2" S cored	04385	



NOZZLE CONNECTOR

Installed on the nozzle outlet, it incorporates a hex opening which matches the hex on Scully's all weather caps. It is all you need to complete the Unifil Tightfill Connection System. Look for the Scully name to make sure you're getting a quality Scully nozzle connector.

UF-37	1 1/4" NPT	04323	
UF-46	1 1/2" NPT	04327	
UF-122	Special threads for Sculflow Nozzle	04346	

O-RING PACKAGE (Qty.3)

The nozzle connector O-ring is fabricated from a high cost compound for maximum life. The O-ring can be easily replaced with a nail file, penknife or pencil on the job if necessary. We suggest a package of the O-rings be carried in the glove compartment of the cab. (Qty.3)

UF-32V	Flourosilicone	04318	
--------	----------------	-------	--



Description	Model #	Size	Part #
-------------	---------	------	--------



INSERT WRENCH

This may be used at installations where the sunken fill box does not permit use of the flush insert connector for tightening or loosening the flush insert cap.

UF-327	-	04360
--------	---	-------

HEX DRIVER

One side of the hex driver is used to install all standard adaptors by inserting the adaptor and turning against the internal lugs. The other side is used for installation of flush insert adaptors.

UF-309	-	04355
--------	---	-------



SPOUT

This accessory spout quickly attaches to the nozzle connector. It is used for troublesome fills or where a loose connection is desired.

UF-54	UNIFIL	04334
NS 204	1 1/4" x 8"	06302
NS 276	1 1/2" x 6.5"	06303

FLUSH BOX COVER

This vertical decorative cover mounts on the house siding to hide the fill pipe. Louvres are built to provide venting and shelter from rain.

UF-339	1 1/2"	04362
--------	--------	-------



FLUSH INSERT ADAPTOR

It is used with sidewalk or other flush fills and designed to insert into the existing fill box. It can be adapted to worn pipe threads by using one of three sizes: standard (S, coded blue), large (L, coded green) and extra-large (XL, coded red).

UF-10S	2" S-NY	04303
UF-10L	2" L-NY	04301
UF-XL	2" XL-NY	04304

FLUSH INSERT CONNECTOR AND WRENCH

Used only when making a tight connection to the Unifil flush insert adaptor. It turns quickly into the flush insert adaptor, then the nozzle connector is rapidly attached to the nozzle. The projections on the side act as a wrench to tighten or loosen the flush insert cap.

UF-306	-	04358
--------	---	-------



FLUSH INSERT CAP

This cap is designed for use with the flush insert adaptor and acts as an effective watershed. It is ideal for use in areas where flush characteristics are important. Because of its use in sunken fill boxes, this cap is supplied with a special, non-swelling gasket.

UF-22	2" NY	04317
-------	-------	-------

CAP IDENTIFICATION DISCS

API color coded symbol styles for #2 fuel oil used for fill pipe identification. Company name and phone number. Installs easily in Scully all weather and flush fill caps.

Name/#	300 Pcs.	04343
	500 Pcs.	10720
	1000 Pcs.	10719

